### What is different about the frame compared to previous versions?

New Roscoe gets a lot rowdier with these frame updates:

Geometry – Longer reach (about 45 mm more, depending on size), slacker 65-degree head angle, steeper 74.7-degree seat tube angle and 430 mm stays.

Fork travel – New Roscoe has 140 mm of front suspension on all sizes.

Other rad features – Boost 148 rear thru axle, more dropper insertion, noise-reducing downtube and chainstay armour, ISCG 05 mount, improved internal routing and UDH (universal derailleur hanger – so hot right now)

### Do any frame sizes feature curved top tubes for lower standover?

All sizes have straight top tubes. The longer reach allows a more gradual angle that results in a lower standover on all sizes compared to previous Roscoe.

## Do all frame sizes use the same wheel size?

Most sizes use 29" wheels, but the XS has 27.5" wheels for the best fit.

### What is the maximum tyre size?

29x2.6" (XS: 27.5x2.6")

# Is it compatible with other wheel/tyre sizes?

No.

### How much dropper post insertion does the frame have?

XS – 235 mm

S - 240 mm

M - 255 mm

ML - 260 mm

L - 280 mm

XL - 328 mm

### What type of bottom bracket does it use?

BSA 73 (threaded)

#### Is it compatible with cranks with 30 mm spindles?

Yes, with compatible BB.

# What is the maximum chain ring size? Minimum chain ring size?

Maximum: 52 mm chain line – 32T; 55 mm chain line –34T

Minimum: 52/55 mm chain line – 28T

<sup>\*</sup>Roscoe 6 provides amazing value by utilising a carry-forward frame

# Are these bikes tubeless-compatible? What additional parts are required?

Yes! The Roscoe 7, 8 and 9 all come with a complete tubeless set-up, including rim strips, valves and sealant.

### Does it have any accessory mounts (kickstand, racks, mudguards, lights)?

It has ISCG 05 mounts for a chain guide or bash guard and none of that other stuff, because the Roscoe just wants to rip singletrack. The Roscoe 9 even comes with an upper chain guide.

#### What is the maximum fork travel?

The Roscoe can handle up to 150 mm of fork travel... but can you?

## Is it compatible with 2x drivetrains?

No.

# Which version of Knock Block does it use?

None of them.

## Are all sizes compatible with a water bottle?

Yes!

#### What is the rear brake mount? What is the max rotor size?

160 mm direct mount on all sizes. Adaptable to 180 mm

## What is the hub spacing?

Boost110 front, Boost 148 rear.